



Dimmable high Performance LED downlight for indoors

GreenPerform DN391/392/393/394/395 downlight

GreenPerform is a high performance Led downlight family suitable for use in a series of Lighting applications in Office, Retail and General Area Lighting. Available in a wide variety of lumen packs, color temp and options of all type of dimming(Phase Cut/Analogue/DALI), GreenPerform becomes the perfect solution for downlight applications for professional users.

Benefits

- Multiple options in Dimming
- Wide range of lumen pack and CCT
- Long life of 50K hours
- High colour consistency

Features

- Aluminium heat sink for better heat dissipation
- Higher life class of 50K burning hour
- Available in both Dimming & fixed output
- Low Energy consumption- High Efficacy more than 100lm/ Watt
- Suitable for low ceiling heights
- Wide range of lumen packs (600lm-2000lm)

GreenPerform DN391/392/393/394/395 downlight

Application

- Office Lighting
- Shop/Showroom Lighting
- Corridor Lighting
- Meeting & conference room lighting
- Reception & general area Lighting

Warnings and Safety

- Meant for use in Indoor environment only

Versions



Application conditions	
Ambient temperature range	0 to +45 °C
Approval and application	
Mech. impact protection code	IK02
Ingress protection code	IP20
Operating and electrical	
Input Voltage	220-240 V
General information	
Beam angle of light source	120 °
Protection class IEC	Safety class I (I)
Optical cover/lens type	Polycarbonate
Driver included	Yes
Flammability mark	F
Optic type	No
Initial performance (IEC compliant)	
Init. Color Rendering Index	>80
Initial LED luminaire efficacy	100 lm/W
Mechanical and housing	
Color	White

Controls and dimming

Order Code	Full Product Name	Dimmable
919515810467	DN 392B LED 10S-4000 PSD WH	Yes
919515810469	DN 394B LED 16S-4000 PSD WH	Yes
919515810471	DN 392B LED 10S-3000 PSD WH	Yes
919515810484	DN 392B LED10S-4000 PSU WH	No

Initial performance (IEC compliant)

GreenPerform DN391/392/393/394/395 downlight

Order Code	Full Product Name	Init. Corr. Color Temperature	Initial luminous flux	Initial input power
919515810467	DN 392B LED 10S-4000 PSD WH	6500 K	1000 lm	10.6 W
919515810469	DN 394B LED 16S-4000 PSD WH	4000 K	1600 lm	15.5 W

Order Code	Full Product Name	Init. Corr. Color Temperature	Initial luminous flux	Initial input power
919515810471	DN 392B LED 10S-3000 PSD WH	3000 K	1000 lm	10.6 W
919515810484	DN 392B LED10S-4000 PSU WH	4000 K	1000 lm	10.6 W

