

GreenSpace Flex

RS378Z M55 D78 S-S AJ D

Accessory - GreenSpace Flex

GreenSpace Flex is performance portfolio dedicated to Hospitality segment for GC/GM countries. With modular design concept, the light engines and different trims could have multiply of combination to satisfy diversified customer's requirement.

Product data

General Information	
Beam angle of light source	- °
Light source color	-
Optic type	No [-]
Optical cover/lens type	No [-]
Control interface	-
Cable	-
Protection class IEC	-
Glow-wire test	60030 [Temperature 600 °C, duration 30 s]
Flammability mark	NO [-]
CE mark	-
ENEC mark	-
Warranty period	3 years
Constant light output	No
Number of products on MCB of 16 A type B	-
Light source engine type	-
Operating and Electrical	
Input Voltage	- V
Input Frequency	- Hz

Power Factor (Min)	-
Mechanical and Housing	
Housing Material	Aluminum
Optical cover/lens material	-
Fixation material	Aluminum
Optical cover/lens finish	-
Overall length	85 mm
Overall width	85 mm
Overall height	52 mm
Overall diameter	0 mm
Color	White
Dimensions (Height x Width x Depth)	52 x 85 x 85 mm (2 x 3.3 x 3.3 in)
Approval and Application	
Ingress protection code	- [-]
Mech. impact protection code	IK04 [0.5 J standard plus]
Initial Performance (IEC Compliant)	
Init. Corr. Color Temperature	- K
Init. Color Rendering Index	-


Greenspace Flex

Initial input power	- W
Application Conditions	
Ambient temperature range	-20 to +45 °C
Maximum dim level	Not applicable
Product Data	
Full product code	911401721722
Order product name	RS378Z M55 D78 S-S AJ D

Order code	911401721722
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	48
Material Nr. (12NC)	911401721722
Net Weight (Piece)	0.120 kg



Dimensional drawing



GreenSpace FLEx_RS378Z

