

# GreenSpace Flex

## RS378Z M55 D60 R-R FX

### Accessory - GreenSpace Flex

GreenSpace Flex is performance portfolio dedicated to Hospitality segment for GC/GM countries. With modular design concept, the light engines and different trims could have multiply of combination to satisfy diversified customer's requirement.

#### Product data

General Information	
Light source color	-
Optical cover/lens type	No [-]
Control interface	-
Cable	-
Protection class IEC	-
CE mark	-
Warranty period	3 years
Constant light output	No
Number of products on MCB of 16 A type B	-
Light source engine type	-
Operating and Electrical	
Input Voltage	- V
Input Frequency	- Hz
Power Factor (Min)	-
Mechanical and Housing	
Housing Material	Aluminum
Optical cover/lens material	-
Fixation material	Aluminum

Optical cover/lens finish	-
Overall length	0 mm
Overall width	0 mm
Overall height	27 mm
Overall diameter	68 mm
Color	White
Dimensions (Height x Width x Depth)	27 x 0 x 0 mm (1.1 x 0 x 0 in)

#### Approval and Application

Ingress protection code	- [-]
Mech. impact protection code	IK04 [ 0.5 J standard plus]

#### Initial Performance (IEC Compliant)

Init. Corr. Color Temperature	- K
Init. Color Rendering Index	-
Initial input power	- W

#### Application Conditions

Ambient temperature range	-20 to +45 °C
Maximum dim level	Not applicable

# Greenspace Flex


## Product Data

Full product code	911401721772
Order product name	RS378Z M55 D60 R-R FX
Order code	911401721772
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	48

Material Nr. (12NC)	911401721772
Net Weight (Piece)	0.040 kg

IK04

## Dimensional drawing



Cut out: Ø60

GreenSpace FLeX\_RS378Z

