

# GreenSpace Flex

## RS378Z M55 D75 S-S FX WP

### Accessory - GreenSpace Flex

GreenSpace Flex is performance portfolio dedicated to Hospitality segment for GC/GM countries. With modular design concept, the light engines and different trims could have multiply of combination to satisfy diversified customer's requirement.

#### Product data

General Information	
Light source color	-
Optical cover/lens type	No [-]
Control interface	-
Cable	-
Protection class IEC	-
CE mark	-
Warranty period	3 years
Constant light output	No
Number of products on MCB of 16 A type B	-
Light source engine type	-
Operating and Electrical	
Input Voltage	- V
Input Frequency	- Hz
Power Factor (Min)	-
Mechanical and Housing	
Housing Material	Aluminum
Optical cover/lens material	-
Fixation material	Aluminum

Optical cover/lens finish	-
Overall length	88 mm
Overall width	88 mm
Overall height	48 mm
Overall diameter	0 mm
Color	White
Dimensions (Height x Width x Depth)	48 x 88 x 88 mm (1.9 x 3.5 x 3.5 in)
Approval and Application	
Ingress protection code	- [-]
Mech. impact protection code	IK04 [ 0.5 J standard plus]
Initial Performance (IEC Compliant)	
Init. Corr. Color Temperature	- K
Init. Color Rendering Index	-
Initial input power	- W
Application Conditions	
Ambient temperature range	-20 to +45 °C
Maximum dim level	Not applicable

# Greenspace Flex



## Product Data

Full product code	911401721862
Order product name	RS378Z M55 D75 S-S FX WP
Order code	911401721862
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	48

Material Nr. (12NC)	911401721862
Net Weight (Piece)	0.140 kg

IK04

## Dimensional drawing



Cut out: 75x75

GreenSpace FLeX\_RS378Z

