



# Greenspace Flex

## RS378B P6 930 PSD-E WB M55

Greenspace Flex, 6 W, 930 warm white, DALI, Finger-protected

GreenSpace Flex is performance portfolio dedicated to Hospitality segment for GC/GM countries. With modular design concept, the light engines and different trims could have multiply of combination to satisfy diversified customer's requirement.

### Product data

General Information		Temperature	
Light source engine type	LED	Ambient temperature range	-20 to +45 °C
CE mark	-		
Light Technical		Controls and Dimming	
Luminous Flux	438 lumen	Dimmable	Yes
Correlated Color Temperature (Nom)	3000 K	Control interface	DALI
Luminous Efficacy (rated) (Nom)	73 lm/W		
Color rendering index (CRI)	>90	Mechanical and Housing	
Light source color	930 warm white	Housing Material	Aluminum Alloy
Optical cover/lens type	-	Optical cover/lens material	-
		Housing Color	Dark gray
		Optical cover/lens finish	-
Operating and Electrical		Approval and Application	
Input Voltage	220 to 240 V	Ingress protection code	IP20 [Finger-protected]
Line Frequency	50 or 60 Hz	Mech. impact protection code	IK04 [0.5 J standard plus]
Power Consumption	6 W	Protection class IEC	Safety class II
Power Factor (Fraction)	0.83		
Number of products on MCB of 16 A type B	-	Initial Performance (IEC Compliant)	
		Luminous flux tolerance	+/-10%

## Greenspace Flex

Power consumption tolerance	+/-10%
-----------------------------	--------

### Product Data

Full product code	911401535471
Order product name	RS378B P6 930 PSD-E WB M55
Order code	911401535471

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	36
Material Nr. (12NC)	911401535471
Full product name	RS378B P6 930 PSD-E WB M55

## Dimensional drawing

