



GreenUp Magnetic Flex

ST307M TG P15 940 PSU-E MB

GreenUp Magnetic Flex, 15 W, 940 neutral white, Finger-protected

Retail & Hospitality has a clear trend that clusters of choices is one of the most important DNAs that being strongly expected in this specific applications. GreenUp Magnetic Flex is a comprehensive product family with magnetic design which supports an easier and flexible way of installation and commissioning. It offers a complete range of options with product diversity and control availability. GreenUp Magnetic Flex gives you a plenty of flexibility to create the lighting magics.

Product data

General Information		Inrush current	
Light source engine type	-		0.15 A
CE mark	-	Power Consumption	15 W
Light Technical		Power Factor (Fraction)	0.9
Luminous Flux	1,275 lumen	Number of products on MCB of 16 A type B	-
Correlated Color Temperature (Nom)	4000 K	Temperature	
Luminous Efficacy (rated) (Nom)	85 lm/W	Ambient temperature range	-20 to +40 °C
Color rendering index (CRI)	>90	Controls and Dimming	
Light source color	940 neutral white	Dimmable	No
Optical cover/lens type	Polycarbonate bowl/cover	Control interface	-
Operating and Electrical		Mechanical and Housing	
Input Voltage	48 V	Housing Material	Aluminium
Line Frequency	- Hz	Optical cover/lens material	Polycarbonate

GreenUp Magnetic Flex

Housing Color	Black
Optical cover/lens finish	Clear
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK03 [0.3 J]
Protection class IEC	Safety class III
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%

Product Data	
Full product code	872016951799899
Order product name	ST307M TG P15 940 PSU-E MB
Order code	911401548632
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	911401548632
Full product name	ST307M TG P15 940 PSU-E MB
EAN/UPC - Case	8720169518605
EAN/UPC - Product/Case	8720169517998

Dimensional drawing

