



UNIUrban

BSS461 LED40 NW 110-277V CLASSIC

UNIUrban is ideal for the urban lighting across the sidewalks, parks, gardens, residential areas, shopping center plazas. Its exquisite, stylish yet classic design is not only suitable for modern cities but also for historical architecture.

Product data

General Information	
Light source color	Neutral white
Light source replaceable	No
Driver included	Yes
Optical cover/lens type	PC-MLO [Polycarbonate micro lens optic]
Control interface	-
Connection	Flying leads/wires
Cable	Cord 0.6 m without plug
Protection class IEC	Safety class I (I)
Flammability mark	NO [-]
CE mark	CE mark
Constant light output	No
Light source engine type	LED
Serviceability class	Class A, luminaire is equipped with serviceable parts
	(when applicable): LED board, driver, control units,
	surge protection device, optics, front cover and
	mechanical parts
Light Technical	
Standard tilt angle posttop	-
Operating and Electrical	
Input Voltage	110 to 277 V
Input Frequency	50 to 60 Hz

Power Factor (Min)	0.95	
Controls and Dimming		
Dimmable	No	
Mechanical and Housing		
Housing Material	Aluminum	
Optical cover/lens material	Tempered glass	
Mounting device	Catenary pole 35mm with Ø 10mm hole	
Optical cover/lens finish	Clear	
Overall height	371 mm	
Overall diameter	482 mm	
Color	Gray	
Approval and Application		
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]	
Mech. impact protection code	IK08 [5 J vandal-protected]	
Initial Performance (IEC Compliant)		
Initial luminous flux (system flux) 4000 lm		
Luminous flux tolerance	+/-10%	
Initial LED luminaire efficacy	120 lm/W	
Init. Corr. Color Temperature	4000 K	
Init. Color Rendering Index	≥70	

Datasheet, 2020, June 22 data subject to change

UNIUrban


Initial input power	33 W
Power consumption tolerance	+/-10%
Application Conditions	
Ambient temperature range	-40 to +50 °C
Ambient temperature range	-40 to 130 C

Order code	911401727752	
Numerator - Quantity Per Pack	1	
Numerator - Packs per outer box 1		
Material Nr. (12NC)	911401727752	
Net Weight (Piece)	7.649 kg	



Product Data	
Full product code	911401727752
Order product name	BSS461 LED40 NW 110-277V CLASSIC

Dimensional drawing



UNIUrban BDP461/BGP461/BSP461/BSS461



© 2020 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.